



Description

Rotel's "06" Series has become an enduring staple of the European audio enthusiast marketplace. The combination of understated appearance, compact size and surprisingly powerful sound has earned these models critical praise and commercial success.

With increased North American interest in affordable performance stereo systems, Rotel of America is pleased to introduce the latest versions of two popular models in the "06" series, the RA-05SE integrated amplifier and the RCD-06SE CD player. Both deliver a full measure of Rotel's 'performance beyond expectation' legacy at the modest retail price of \$599 each.

The RA-05SE integrated amplifier shares much of its design heritage with the flagship 15 series from Rotel. Although the RA-05SE is very affordable, there are no shortcuts taken where sound quality is concerned. At Rotel, we understand well that small design changes can make a big difference. So it is with the Rotel RA-05SE, where time spent tuning, upgrading, and selecting better components has resulted in very impressive performance.

Significant sonic improvements have resulted from a major update to the power supply, specifically the way it is decoupled from the input switching and buffer stages. The input filter capacitors in the buffer stages have also been updated, as have the buffer stage input and output series signal handling resistors. All these carefully considered design changes were followed by extensive listening evaluations. The result is an integrated amplifier that can provide exceptional music enjoyment, especially when matched with the RCD-06SE CD player.

Specifications

Continuous Power Output (20-20kHz, <0.03%, 8Ω)	40 Watts/ch	Input Overload	180mV
Total Harmonic Distortion (20Hz-20kHz)	<0.03% at rated power 1/2 power or 1 Watt	Phone Input	5V
Intermodulation Distortion (60Hz : 7kHz, 4:1)	<0.03% at rated power, 1/2 power or 1 Watt	Line Level Inputs	1V / 470Ohms
Frequency Response		Preamp Output / Impedance	1V / 470Ohms
Phone Input	20Hz-15kHz +/- 0.3 dB	Tone Controls - Bass / Treble	+/-6dB at 100Hz / 10kHz
Line Level Inputs	10Hz-40kHz, +/- 1 dB	Signal to Noise Ratio (IHF "A" weighted)	
Damping Factor (20-20,000Hz, 8Ω)	180	Phone Input	80dB
Input Sensitivity / Impedance		Line Level	100dB
Phone Input	2.5mV / 47kOhms	Power Requirements	230 Volts, 50Hz
Line Level Inputs	150mV / 24kOhms	Powers Consumption	220 Watts
		Dimension (W, H, D)	437 x 72 x 342 mm
		Weight (net)	5.9kg / 13lbs

www.rotel.com

The Rotel Co. Ltd.
10-10 Shinsen-Cho
Shibuya-Ku,
Tokyo 150, Japan

Rotel of America
54 Concord St.
N. Reading, MA 01864
USA
T +1 978 664 3820
F +1 978 664 4109

Rotel Europe
Dale Road
Worthing
West Sussex BN11 2BH, UK
T +44 (0) 1903 221 763
F +44 (0) 1903 221 525