ROTEL

RA-1572MKII

STEREO INTEGRATED AMPLIFIER

AMPLIFYING SOUND. ELEVATING LIFE.™



TESTED

Certified Roon Tested ADM AA

Supports MQA and MQA Studio

 \sim

2 x 200 Watts of robust Class AB power, 4 Ohms Oj|

Moving Magnet Phono input for turntable connection Wireless aptX™ and AAC Bluetooth



Texas Instruments premium 32-bit/384kHz Digital to Analog Converter

The RA-1572MKII Integrated Amplifier is an essential component for music lovers leveraging the best of Rotel's analog and digital technologies bringing music to life with exceptional fidelity. The role of an integrated amplifier continues to evolve with the RA-1572MKII optimized in every aspect including the power amplifier delivering 120 Watts of robust Class AB output into 8 ohms, audio circuit design innovations, premium audiophile Digital to Analog Converter and a full complement of source inputs.

As typical of Rotel amplifiers, the RA-1572MKII utilizes an in-house manufactured oversized toroidal transformer. The toroidal transformer's shape helps prevent stray radiation patterns from corrupting audio signals as they pass through adjacent circuits. The transformer feeds a bank of 4 low ESR, high efficiency, T-Network slit-foil storage capacitors for deep, controlled bass energy.

The RA-1572MKII support digital sources utilizing a Texas Instruments 32-bit/384kHz DAC with critically tuned output filter circuits rendering even the most subtle detail. The preamplifier circuits and linear amplifier gain stages have been custom

engineered ensuring natural detail, agility and an immersive soundstage. Analog, digital, PC-USB supporting MQA, aptX™ and AAC wireless Bluetooth streaming, XLR Balanced and Moving Magnet Phono stage inputs ensures connection to your favorite sources.

The RA-1572MKII is certified Roon Tested delivering the best experience using Roon software so you can just enjoy the music.

The front panel includes a status display, source and volume controls, Speaker A-B selection for Zone 2, and 3.5mm headphone jack. Ethernet and RS232 connections allow seamless integration with control systems and software updates.

ROTEL

RA-1572MKII

STEREO INTEGRATED AMPLIFIER

AMPLIFYING SOUND, ELEVATING LIFE. $^{\text{TM}}$



SPECIFICATIONS

Maximum Power Output	200 watts / ch (4 ohms)	Digital Section	
Continuous Power Output	120 watts/ ch (8 ohms)	Frequency Response	10 Hz - 90k Hz (0 ± 2 dB, Max)
Total Harmonic Distortion	< 0.018%	Signal to Noise Ratio (IHF "A" weighted)	100 dB
Intermodulation Distortion (60 Hz : 7k Hz, 4:1)	< 0.03%		
		Input Sensitivity/Impedance	0 dBFs / 75 ohms
Frequency Response		Preamplifier Output Level	1.42 V (at -20 dB)
Phono Input	20 Hz-20k Hz (0 ±0.5 dB)	Coaxial/Optical Digital Signals	SPDIF LPCM
Line Level Inputs	10 Hz-100k Hz (0 ±0.5 dB)		(up to 24-bit / 192k Hz)
Damping Factor (20 Hz-20k Hz, 8 ohms)	300	PC-USB	USB Audio Class 1.0 (up to 24-bit / 96k Hz)
Input Sensitivity / Impedance			USB Audio Class 2.0
Phono Input (MM)	2.1 mV / 47k ohms		(up to 32-bit / 384k Hz)* *Driver installation required
Line Level Inputs (RCA)	270 mV / 100k ohms		MQA and MQA Studio
Line Level Inputs (XLR)	440 mV / 100k ohms		(up to 24-bit / 384k Hz)
Input Overload			Roon Tested
Phono Input (MM)	32 mV	Power Requirements	
Line Level Inputs (RCA)	4 V	Europe USA	230 V, 50 Hz 120 V, 60 Hz
Line Level Inputs (XLR)	5.5 V	Power Consumption	400 watts
Preamplifier Output / Impedance	1.5 V / 470 ohms	Standby Power Consumption	
Signal to Noise Ratio (IHF "A" weighted)		Normal Network Wakeup	< 0.5 watts < 2 watts
		PTU (4 ohms 1/9th nower)	910 RTII/b

All specifications are accurate at the time of printing. Rotel reserves the right to make improvements without notice.

80 dB

100 dB

Phono Input (MM)

Line Level Inputs

MQA and the Sound Wave Device are registered trade marks of MQA Limited. © 2016 Being Roon Tested means that Rotel and Roon have collaborated to ensure you have the best experience using Roon software and the Rotel equipment together, so you can just enjoy the music.

810 BTU/h

431 x 144 x 358 mm

17 x 5 5/8 x 14 1/8 in

13.63 kg, 30.05 lb

Silver and Black

3U / 132.6mm / 5 1/4 in

BTU (4 ohms, 1/8th power)

 $\textbf{Dimensions} \; (\mathsf{W} \; \mathsf{X} \; \mathsf{H} \; \mathsf{X} \; \mathsf{D})$

Front Panel Height

Weight (net)

Finish