

ROTEL

STEREO INTEGRATED AMPLIFIER

A11 Tribute



2 x 50 Watts (8 Ohms)
of classic Rotel Class
AB power



Includes remote
control



Moving Magnet
Phono input for
turntable connection



Bluetooth with
apt-X and AAC



Texas Instruments Digital
to Analogue Converter

The A11 Tribute is a Class AB 50W (8 ohms) Integrated Amplifier developed in cooperation with the audio engineering legend Ken Ishiwata as a Tribute to his legacy spanning over 40 years in the industry.

The collaboration between Ken and Rotel's own engineering design teams delivered on the promise of an even higher level of performance of the extremely successful and popular award-winning A11. Upgraded components and meticulous tuning of

all critical circuits deliver a richer, more expressive, and true-to-life experience from all of the support source inputs including apt-X and AAC wireless Bluetooth, array of 4 RCA analog inputs and a Moving Magnet Phono stage for vinyl fans.

The front panel graphic display and IR remote ensure effortless control of the audio driven by a Rotel in-house manufactured oversized toroidal transformer. The resulting acoustic performance speaks for itself under all loading conditions with even the most difficult speaker loads.

Rotel integrated
amplifiers bring your
sources to life with
amazing fidelity.
See more at

rotel.com



ROTEL

STEREO INTEGRATED AMPLIFIER

A11 Tribute



SPECIFICATIONS

Continuous Power Output (20 - 20kHz, < 0.03%, 8 ohms)	50 watts/ch	Tone Controls - Bass / Treble	± 10 dB at 100 Hz / 10k Hz
Total Harmonic Distortion (20 Hz - 20 kHz at rated power)	< 0.03%	Signal to Noise Ratio ("A" weighting)	
Intermodulation Distortion (60 Hz : 7kHz, 4:1)	< 0.03%	Phono Input	85 dB
Frequency Response		Line Level Inputs	100 dB
Phono Input	20 Hz - 20k Hz, ± 0.5 dB	General	
Line Level Inputs	10 Hz - 100k Hz, ± 0.5 dB	Power Requirements	
Damping Factor (20 - 20,000 Hz, 8 ohms)	140	Europe	230 V, 50 Hz
Input Sensitivity / Impedance		USA	120 V, 60 Hz
Phono Input	2.3 mV / 47k Ohms	Power Consumption	160 watts
Line Level Inputs	180 mV / 47k Ohms	Standby Power Consumption	< 0.5 watts
Input Overload		BTU (4 ohms, 1/8 power)	479 BTU/h
Phono Input	50 mV	Finishes	Silver and Black
Line Level Inputs	4 V	Dimensions (W x H x D)	430 x 93 x 345 mm 17" x 3 5/8" x 13 1/2"
Preamp Output / Impedance	1 V / 470 Ohms	Front Panel Height	80 mm, 3 1/8"
		Weight (net)	6.85 kg, 15.1 lb

Rotel integrated amplifiers bring your sources to life with amazing fidelity. See more at

rotel.com

