



2 x 40 Watts of robust power, 4 Ohms



Class AB amplifier design



Moving Magnet Phono Stage input for turntable connection



High current power supply



Includes remote control

The A8 Integrated Amplifier is the perfect fusion of power, size, efficiency, and value tailored for music enthusiasts.

Built around an in-house manufactured, high current, Rotel-crafted toroidal power transformer, the A8 delivers a commanding 40 Watts per channel of Class A/B power into 4 ohms. The high efficiency output drive transistors ensure deep bass energy is controlled with ultimate precision while comfortably maintaining composure at all listening levels.

The A8 features three line-level RCA inputs connecting your favorite analogue sources complemented by a Moving Magnet compatible Phono Stage to spin classic vinyl albums. For private listening, a front panel 1/8" headphone jack is also included.

The included IR remote ensures precise and seamless operation of the volume level and selection of the desired source input all from your favorite listening position. The remote also conveniently includes CD transport control functions supporting Rotel CD players.

Personal selection of LED volume indicator color allows the A8 to be tailored to both mood and environment. Choose from Red, Green, Blue, or Purple LED colors fitting comfortably into any environment. Get hands-on with the front panel Bass, Treble and Balance controls to personalize the listening experience with your music.

Rear panel 5-way speaker binding posts provide the ultimate installation flexibility and connection to your loudspeakers.

Available in both stylish black and sophisticated silver variants, the A8 integrates the power, versatility, and elegance of your audio experience.



SPECIFICATION

Power Output	30 watts / ch (8 ohms) 40 watts / ch (4 ohms)	Power Requirements	
Total Harmonic Distortion (20 Hz - 20k Hz)	< 0.03%	USA	120 V, 60 Hz
Intermodulation Distortion (60 Hz : 7k Hz, 4:1)	< 0.03%	EU	230 V, 50 Hz
Frequency Response		Power Consumption	110 Watts
Phono input	20 Hz - 20k Hz, -0.5 dB, +0 dB	Standby Power Consumption	< 0.5 watts
Line Level Inputs	10 Hz - 100k Hz, -0.5 dB, +0 dB	BTU (4 ohms, 1/8 power)	340 BTU/h
Damping Factor (20 - 20,000 Hz, 8 ohms)	80	Dimensions (W, H, D)	430 x 73 x 347 mm 17" x 2 7/8" x 13 5/8"
Input Sensitivity / Impedance		Panel Height	60 mm / 2 3/8"
Phono input	2.5 mV / 40k Ohms	Weight (net)	5.8 kg, 12.8 lbs.
Line Level Inputs	180 mV / 60k Ohms	Finish	Black and Silver
Input Overload			
Phono input	50 mV		
Line Level Inputs	4 V		
Tone Controls - Bass / Treble	± 6 dB at 100 Hz / 10k Hz		
Signal to Noise Ratio (IHF "A" weighted)			
Phono input	80 dB		
Line Level Inputs	90 dB		