

MICHI

X5 Series 2

STEREO INTEGRATED AMPLIFIER



ROON
TESTED

Certified
Roon Tested



Supports MQA
and MQA Studio



2 x 600 Watts of
robust power,
4 ohms



Class AB amplifier
design



Bluetooth with
aptX™ HD and AAC



ESS premium 32-bit
8-Channel Digital to
Analog Converter

The Michi X5 Series 2 Integrated Amplifier is music reproduction reimagined. Thanks to a meticulous balance of innovation and critical audio engineering applied to every circuit, signal path, and electronic component, the Michi X5 Series 2 is capable of delivering a breathtaking 600 Watts of Class AB output power into 4 ohms under even the most demanding conditions.

Connect all your favorite music sources including Analog RCA and XLR Balanced, Moving Magnet or Moving Coil Phono, aptX™ HD Wireless Bluetooth, Coaxial and Optical. The PC-input supports PCM (32-bit 384kHz) and Quad DSD (11.2MHz) with full MQA hardware decoding up to 24-bit 384kHz.

An ESS SABRE ES9028PRO 8-Channel Digital to Analog converter is configured for stereo decoding, dedicating 4 channels each to the left and right audio signals rendering music with exceptionally accurate timing and an immersive soundstage which reveals the finest of details.

The Michi X5 Series 2 is powered by dual oversized in-house manufactured, shielded, low noise toroidal transformers feeding a bank of 4 parallel-aligned 22,000uF high-efficiency storage

reservoir capacitors. Custom power supplies isolate drive current to critical analog and digital circuits delivering an ultra-quiet noise floor with exceptional control of deep bass energy while maintaining finesse and clarity of the midrange and high frequencies.

The high-resolution graphic display is configurable to show a Graphic EQ or Peak Power Meter and ensures easy setup and configuration. Custom front panel controls and the elegant Michi-series IR remote assures seamless operation from the comfort of your listening chair.

Dual Platinum-plated custom Michi speaker binding posts support traditional and bi-wire installations. A full size ¼" (6.35mm) front panel headphone connection is available for private listening sessions.

RS232 and Ethernet ports provide compatibility with all popular control systems.

Michi, expectations amplified.

MQA and the Sound Wave Device are registered trade marks of MQA Limited. © 2016
Being Roon Tested means that Rotel and Roon have collaborated to ensure you have the best
experience using Roon software and the Rotel equipment together, so you can just enjoy the music.

MICHI

X5 Series 2

STEREO INTEGRATED AMPLIFIER



SPECIFICATIONS

Maximum Power Output	600 watts/channel (4 ohms)
Continuous Power Output	350 watts/channel (8 ohms)
Total Harmonic Distortion	< 0.009%
Intermodulation Distortion (60 Hz : 7 kHz, 4:1)	< 0.03%
Frequency Response	
Phono Input	20 Hz-20k Hz (+0 dB, -0.2 dB)
Line Level Inputs	10 Hz-100k Hz (+0 dB, -0.6 dB)
Damping Factor (20 Hz - 20kHz, 8 ohms)	350
Input Sensitivity / Impedance	
Phono Input (MM)	5.7 mV / 47k ohms
Phono Input (MC)	570 uV / 100 ohms
Line Level Inputs (RCA)	380 mV / 100k ohms
Line Level Inputs (XLR)	580 mV / 100k ohms
Input Overload	
Phono Input (MM)	197 mV
Phono Input (MC)	19 mV
Line Level Inputs (RCA)	12.5 V
Line Level Inputs (XLR)	12.5 V
Preamplifier Output Level / Impedance	1 V / 470 ohms
Tone Controls	
Bass	±10 dB at 100 Hz
Treble	±10 dB at 10k Hz
Signal to Noise Ratio (IHF "A" weighted)	
Phono Input (MM/MC)	80 dB
Line Level Inputs	102 dB
Channel Separation	
Phono Input (MM)	> 65 dB
Line Level Inputs	> 65 dB

Digital Section	
Frequency Response	20 Hz - 20k Hz (0 ± 0.4 dB)
Signal to Noise Ratio (IHF "A" weighted)	102 dB
Input Sensitivity/Impedance	0 dBFs / 75 ohms
Preamplifier Output Level	1.2 V (at -20 dB Volume Position)
Coaxial/Optical Digital Signals	SPDIF LPCM (up to 192kHz 24 bit)
PC-USB	USB Audio Class 1.0 (up to 96kHz 24-bit) USB Audio Class 2.0 (up to 384kHz 32-bit)* *Driver installation required
	DSD and DoP support MQA and MQA Studio support Room Tested
Power Requirements	
Europe	230 V, 50 Hz
USA	120 V, 60 Hz
Power Consumption	850 watts
Standby Power Consumption	
Normal	< 0.5 watts
Network Wakeup	< 2 watts
BTU (4 ohms, 1/8 power)	2194 BTU/h
Dimensions (W x H x D)	485 x 195 x 452 mm 19" x 7 5/8" x 17 3/4"
Front Panel Height	177 mm / 7"
Weight (net)	43.8 kg, 96.56 lb
Finish	Black

All specifications are accurate at the time of printing.
Michi reserves the right to make improvements without notice.