

# MICHI

## X430

### INTEGRATED AMPLIFIER



2 x 340 Watts of robust power, 4 ohms



Bluetooth with aptX™ HD and AAC



Certified Roon Tested



ESS premium 32-bit Digital to Analog Converter



Includes remote control

The Michi Prestige X430 Integrated Amplifier represents uncompromising power, precision engineering, and refined craftsmanship. The X430 delivers a formidable 340 Watts per channel into 4 ohms loudspeakers (210 Watts into 8 ohms). The Class AB output stages utilize custom tuned push-pull high-current output transistors, revealing dynamics with impeccable control that can drive even the most demanding loudspeakers.

At the heart of the X430 is a premium ESS SABRE ES9039Q2M 32-bit DAC, ensuring exceptional transparency and musical accuracy. Digital connectivity includes 3 Coaxial, 3 Toslink Optical, PC-USB (PCM 32-bit/384kHz, DSD 256/4X with DoP) plus aptX™ HD / AAC wireless Bluetooth streaming.

The HDMI ARC input conveniently connects directly to your TV, delivering movies, sports, and games in high fidelity as a seamless 2.1 audio system featuring dual subwoofer outputs and two sets of A-B user-selectable speaker terminals.

For vinyl enthusiasts, the X430 also features a Moving Magnet Phono input, as well as three RCA inputs, to ensure compatibility with all legacy audio sources.

A massive, in-house-manufactured toroidal transformer in a noise-rejecting enclosure drives proprietary power supplies delivering ultra-low noise, minimal distortion, and outstanding dynamics. Critical circuits are physically and electrically isolated throughout the audio path, further enhancing signal integrity.

The Michi X430 pairs mechanical excellence with visual elegance. Its anodized aluminum faceplate, top cover, and knurled volume knob are precision-machined for durability and a premium feel. A solid glass front panel with a large, high-resolution color display is user-customizable, featuring both spectrum and VU meter modes for an even more engaging listening experience with a modern finish.

The X430 embodies Michi's passion for musical integrity and uncompromising engineering—designed to unlock the full sonic potential from CD players, dedicated streamers, TV sources, and analogue components alike. One integrated solution that brings every source to life.

Being Roon Tested means that Rotel and Roon have collaborated to ensure you have the best experience using Roon software and the Rotel equipment together, so you can just enjoy the music.

# MICHI

## X430

### INTEGRATED AMPLIFIER



#### SPECIFICATIONS

<b>Power Output (FTC)</b>	220 watts/channel (8 ohms)	<b>Digital Section</b>	
<b>Maximum Power Output (Non FTC)</b>	340 watts/channel (4 ohms)	<b>Frequency Response</b>	10 Hz - 20k Hz (+0,-0.4 dB, Max)
<b>Continuous Power Output (Non FTC)</b>	210 watts/channel (8 ohms)	<b>Signal to Noise Ratio (IHF "A" weighted)</b>	> 110 dB
<b>Total Harmonic Distortion</b>	< 0.03%	<b>Input Sensitivity/Impedance</b>	0 dBFs / 75 ohms
<b>Intermodulation Distortion (60 Hz : 7 kHz, 4:1)</b>	< 0.03%	<b>Preamplifier Output Level</b>	1.15 V (at -20 dB Volume Position)
<b>Frequency Response</b>		<b>Digital to Analog Converter</b>	ESS ES9039Q2M DAC
Phono Input	20 Hz-20k Hz (+0 dB, -0.5 dB)	<b>Coaxial/Optical Digital Signals</b>	SPDIF LPCM (up to 192kHz 24 bit)
Line Level Inputs	10 Hz-100k Hz (+0 dB, -0.5 dB)	<b>PC-USB</b>	USB Audio Class 2.0 (up to 384kHz 32-bit)* *Driver installation required
<b>Damping Factor (20 Hz - 20kHz, 8 ohms)</b>	260		Support DSD (up to 4X, 11.2MHz) and DoP (up to 2X, 5.6MHz)
<b>Input Sensitivity / Impedance</b>			Roon Tested
Phono Input (MM)	5.56 mV / 47k ohms	<b>HDMI</b>	Support CEC with ARC function
Line Level Inputs (RCA)	356 mV / 100k ohms		2-channel PCM only (up to 48 kHz, 24-bit)
Line Level Inputs (XLR)	743 mV / 50k ohms		
<b>Input Overload</b>		<b>Power Requirements</b>	
Phono Input (MM)	66 mV	Europe	230 V, 50 Hz
Line Level Inputs (RCA)	4 V	USA	120 V, 60 Hz
Line Level Inputs (XLR)	10 V	<b>Power Consumption</b>	520 watts
<b>Signal to Noise Ratio (IHF "A" weighted)</b>		<b>Standby Power Consumption</b>	
Phono Input	> 80 dB	Normal	< 0.5 watts
Line Level Inputs (RCA)	> 105 dB	Network Wakeup	< 2 watts
Line Level Inputs (XLR)	> 100 dB	<b>BTU (4 ohms, 1/8th power)</b>	1476 BTU/h
<b>Preamplifier Output Level / Impedance</b>	1.92 V / 100 ohms	<b>Dimensions (W x H x D)</b>	431 x 148 x 422 mm 17 x 6 x 16 1/2 ins
<b>Tone Controls</b>		<b>Front Panel Height</b>	132 mm / 5 1/4 ins
Bass	±10 dB at 100 Hz	<b>Weight (net)</b>	16.9 kg, 37.3 lbs
Treble	±10 dB at 10k Hz	<b>Finish</b>	Black
<b>Channel Separation</b>			
Phono Input	> 55 dB		
Line Level Inputs	> 55 dB		

All specifications are accurate at the time of printing. Michi reserves the right to make improvements without notice.